


HOMOGENEOUS
COMPACT VINYL

Centra 43

CERTIFICATION & CLASSIFICATION	STANDARDS	Centra 43
Classification	ISO 10874 – EN 685	Commercial: 34 Industrial: 43
Type of floor covering	ISO 10581	Homogeneous vinyl flooring. Type I.
ISO certification		Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS	STANDARDS	Centra 43
Total thickness	ISO 24346 – EN 428	2.0 mm
Wear layer thickness	ISO 24340 – EN 429	2.0 mm
Total weight/m²	ISO 23997 – EN 430	3000 g
Surface treatment		PUR Reinforced
TECHNICAL PERFORMANCES	STANDARDS	Centra 43
Residual indentation	ISO 24343-1 – EN 433	≤ 0.1 mm
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{f1} s1 ≥ 8 kW/m ² Pass
Dimensional stability	ISO 23999 – EN 434	≤ 0.40 % for rolls ≤ 0.25 % for tiles
Flexibility	ISO 24344, Method A	No cracking on 20 mm mandrel
Castor chair test	ISO 4918 – EN 425	Suitable
Marine certificate	IMO Res. MSC. 307(88) IMO (2010 FTPC) Annex 1, Part 5 and 2	 0038/2017 MED 1750032/M1 SAS F170035/M1
Antistatic properties	EN 1815	≤ 2 kV
Electrical resistance	EN 1081	R ₁ ≤ 10 ⁹ Ω
Light fastness	EN ISO 105-B02	≥ level 6
Chemical resistance	ISO 26987 – EN 423	Good resistance
Bacteria resistance	ISO 846: Part C	Does not favour growth
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3
Seam strength	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Underfloor heating		Suitable – max 27°C
Form of delivery	ISO 24341 – EN 426 Sheet (rolls)	20 running meters x 200 cm
Colours		18

The above information is subject to modification for the benefit of further improvement (05/2017)