

HOMOGENEOUS  
COMPACT VINYL

## Norma 43

CERTIFICATION & CLASSIFICATION		STANDARDS	Norma 43
<b>Classification</b>		ISO 10874 – EN 685	Commercial: 34 Industrial: 43
<b>Type of floorcovering</b>		ISO 10581 – EN 649	Homogeneous vinyl flooring. Single layered. Type I.
<b>ISO certification</b>			Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS		STANDARDS	Norma 43
<b>Total thickness</b>		ISO 24346 – EN 428	2.0 mm
<b>Wear layer thickness</b>		ISO 24340 – EN 429	2.0 mm
<b>Total weight/m<sup>2</sup></b>		ISO 23997 – EN 430	2700 g
<b>PUR</b>			Yes
TECHNICAL PERFORMANCES		STANDARDS	Norma 43
<b>Residual indentation</b>		ISO 24343-1 – EN 433	Requirement ≤ 0.1 mm
<b>Reaction to fire</b>		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>fl</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass
<b>Dimensional stability</b>		ISO 23999 – EN 434	≤ 0.40 % for rolls ≤ 0.25 % for tiles
<b>Castor chair test</b>		ISO 4918 – EN 425	Suitable
<b>Static electrical charge</b>		EN 1815	≤ 2 kV
<b>Electrical resistance</b>		EN 1081	≤ 10 <sup>9</sup> Ω
<b>Light fastness</b>		EN ISO 105-B02	≥ level 6
<b>Chemical resistance</b>		ISO 26987 – EN 423	Good resistance
<b>Fungi and bacteria resistance</b>		ISO 846: Part C	Does not favour growth
<b>Clean room test</b>		ASTM F24-04 ASTM F51-00	Class A
<b>Slip resistance</b>		DIN 51130 EN 13893	R9 ≥ 0.3
<b>Underfloor heating</b>			Suitable – max 27°C
<b>Form of delivery</b>		ISO 24341 – EN 426 Sheet (rolls)	Approx. 20 running meters x 200 cm
		ISO 24342 – EN 427 Tiles (box)	61.0 x 61.0*cm – 14 tiles/box = 5.21 m <sup>2</sup> 50.0 x 50.0*cm – 24 tiles/box = 6 m <sup>2</sup>
<b>Colours</b>			24

\* Available for orders for at least 700 m<sup>2</sup>

The above information is subject to modification for the benefit of further improvement (03/2015).