

HOMOGENEOUS  
COMPACT VINYL

# Specjal 43 S

CERTIFICATION & CLASSIFICATION		STANDARDS	Specjal 43 S
<b>Classification</b>	ISO 10874 – EN 685		Commercial: 34 Industrial: 43
<b>Type of floor covering</b>	ISO 10581 – EN 649		Homogeneous vinyl flooring. Single layered. Type II.
<b>ISO certification</b>			Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS		STANDARDS	Specjal 43 S
<b>Total thickness</b>	ISO 24346 – EN 428		2.0 mm
<b>Wear layer thickness</b>	ISO 24340 – EN 429		2.0 mm
<b>Total weight/m<sup>2</sup></b>	ISO 23997 – EN 430		3700 g
<b>PU</b>			Yes
TECHNICAL PERFORMANCES		STANDARDS	Specjal 43 S
<b>Residual indentation</b>	ISO 24343-1 – EN 433		Requirement ≤ 0.1 mm
<b>Reaction to fire</b>	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		Class B <sub>fl</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass
<b>Dimensional stability</b>	ISO 23999 – EN 434		≤ 0.40 % for rolls ≤ 0.25 % for tiles
<b>Castor chair test</b>	ISO 4918 – EN 425		Suitable
<b>Static electrical charge</b>	EN 1815		≤ 2 kV
<b>Light fastness</b>	EN ISO 105-B02		≥ level 6
<b>Chemical resistance</b>	ISO 26987 – EN 423		Good resistance
<b>Fungi and bacteria resistance</b>	ISO 846: Part C		Does not favour growth
<b>Clean room test</b>	ASTM F24-04 ASTM F51-00		Class A
<b>Underfloor heating</b>			Suitable – max 27°C
<b>Form of delivery</b>	ISO 24341 – EN 426 Sheet (rolls) ISO 24342 – EN 427 Tiles (box)		Approx. 20 running meters x 200 cm 61.0 x 61.0*cm – 14 tiles/box = 5.21 m <sup>2</sup> 50.0 x 50.0*cm – 24 tiles/box = 6 m <sup>2</sup> 30.0 x 30.0**cm – 50 tiles/box = 4,5 m <sup>2</sup>
<b>Colours</b>			12

\* Available for orders for at least 700 m<sup>2</sup>

\*\* The following Specjal 43 S coverings in tiles are offered on a continuous basis: 21324001; 21324004; 21324008; 21324010; 21324012. The other colours are available for orders for at least 700 m<sup>2</sup>

The above information is subject to modification for the benefit of further improvement (03/2015).